

Flat roof motor

755999

EAN 5414425103416

General information

Motor integrated	•
With sound absorber	-
With isolated roof socket	-
With isolated roof socket and sound absorber	•
With automatic shutter (galvanized)	•
Isolator switch	•

Dimensions (mm) (more detailed info can be found on the website)

Dimensions (WxDxH) (mm)	388 x 388 x 784
Diameter outlet (mm)	-
Diameter inlet (tube)(mm)	150
Diameter inlet (opening roof)(mm)	180

Functions

Operation	in combination with hood
Number of speed	3 + power
Minimum / maximum operating temperature (°C)	- 25 / 65

Airflow and noise level

Maximum flow (m3/h)	1180
---------------------	------

Airflow (m3/h)/ preasure (Pa)(according to EN 61591)

- Speed 1	850/590
- Speed 2	970 /625
- Speed 3	1075/650
- Powerspeed / speed 4	1145/670

Noise Level (dB(A) re 1 pW/ dB(A) re 20µPa) (according to EN 60704-2-13)

- Speed 1	-
- Speed 2	-
- Speed 3	-
- Powerspeed / speed 4	-

Noise level measured on the extract side Lwa5 (dB(A)(DIN 45635-2)

- Speed 1	55
- Speed 2	56
- Speed 3	57
- Powerspeed / speed 4	58

Technical specifications

Total power (W)	191
Position exhaust	vertical
Weight motorunit (kg)	13,9
Material roof fan	aluminium (ALMG3), seawater resistance
Material roof socket	aluminium (ALMG3), seawater resistance
Material automatic shutter	galvanized

Accessories

Extended cable for seperated motor (5m)	7000092
---	---------





